

BIEXSO332H6
BIEXSO363H6
BIEXSO432H3
BIEXSO432H6
BIEXSO532H6
BIEXSO563H6

See current catalogue for further detail

IP67 Extension Socket Range

Trader has introduced a selective range of IP67 extensions sockets in accordance with IEC 60309 and AS/NZS 60309 in the Bison range. The plugs have initially been offered as a solution to interact with fixed sockets in the IEC format offered in several of the TRADER Buffalo range for general use in 6h and refrigerated containers in the 3h format. The Bison range however is much more than just for this purpose and can provide an interactive solution for many other IEC 60309 based products in industry.

The durable structure and hydrant lock provided excellent performance for many applications.



It features easy to assemble and install lock rings, glands and housings making it versatile and robust for industrial use.

As referenced the current offer will be available as IP67 models with the hydrant lock.

There is also a 5 pin (3P +N + E) 63A red models with 6h keyway/earth pin positions for general usage

Cable sizes suited

63A models terminal Diameter 7.1mm for 25mm²

Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

*Cat No. Extension Sockets	Current Rating (A)	Pin Config	Bison Pin Config Code	Max Terminal Cable Diameter (mm)	Max Terminal Cable Size (mm ²)	Matching Plug Straight / Angled
BIEXSO332H6	32	3	A	7.15	25	BIP332H6
BIEXSO363H6	63	3	B	7.15	25	BIP363H6
BIEXSO432H3	32	4	D	7.15	25	BIP432H3
BIEXSO432H6	32	4	C	7.15	25	BIP432H6
BIEXSO532H6	32	5	E	7.15	25	BIP532H6
BIEXSO563H6	63	5	F	7.15	25	BIP563H6



Certification Number:

GMA-524469

GSM Electrical (Australia) Pty Ltd

5-9 Rundle Street, Kent Town SA 5067

P: 1300 301 838 | E: service@gsme.com.au

www.gsme.com.au

