

BIP432H3 BIP432H6 BIP563H6

See current catalogue for further detail

IP67 Plug Range

Trader has introduced a selective range of IP67 plugs in accordance with IEC 60309 and AS/NZS 60309 in the Bison range. The plugs have initially been offered as a solution to interact with fixed sockets in the IEC format offered in several of the TRADER Buffalo range for general use in 6h and refrigerated containers in the 3h format.

The Bison range however is much more than just for this purpose and can provide an interactive solution for many other IEC 60309 based products in industry.

The durable structure and hydrant lock provided excellent performance for many applications.



It features easy to assemble and install lock rings, glands and housings making it versatile and robust for industrial use. Quick release mechanism for opening on 32A models.

As referenced the current offer will be available as IP67 models with the hydrant lock.

The initial range consists of 4 pin (3P + E) 32A red model with 6h keyway/earth pin positions for general usage.

There is also a 4 pin (3P + E) 32A red model with 3h keyway/ earth pin position for refrigerated container applications

There is also a 5 pin (3P + N + E) 63A red models with 6h keyway/earth pin positions for general usage

Cable sizes suited

32A models terminal Diameter 5.2mm for 16mm²

63A models terminal Diameter 7.1mm for 25mm²

Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

*Cat No. Plugs	Current Rating (A)	Pin Config	Bison Pin Config Code	Max Terminal Cable Diameter (mm)	Max Terminal Cable Size (mm ²)	Matching Plug Straight / Angled
BIP432H3	32	4	C	5.2	16	N/A
BIP432H6	32	4	B	5.2	16	N/A
BIP563H6	63	5	E	7.15	25	BIEXSO563H6



Certification Number:

GMA-524468

GSM Electrical (Australia) Pty Ltd

Level 2, 142-144 Fullarton Road, Rose Park SA 5067

P: 1300 301 838 | E: service@gsme.com.au

www.gsme.com.au

