

EV Fleet 22kW AC Charger

Fleet22



Fleet22

Tech Specs

Charging Power	Up to 7.4kW (1P) or 22kW (3P)
Connector Type	Type 2 or 1
Maximum Output Current	32 amps per phase
Nominal AC Frequency	50 Hz / 60 Hz
Input Voltage	110 to 230 V AC (L-N)
Operating Temperature	From -25°C to +55°C
Relative Humidity	Max. 95% non-condensing
Ingress Protection	IP65
Cable Length	Up to 5m (Standard). Other lengths optional.
Impact Protection	IK10
Dimensions (DxW)	380×100mm
Weight (including cable)	6.5kg
Wireless Communication	Wi-Fi 2.4GHz IEEE 802.11.b/g/n Bluetooth 4.1, Ethernet 10/100M optional: 4G (LTE Cat M1)
Communication Protocol	OCPP 1.6j, upgradable to 2.0
Storage Temperature	From -30°C to 85°C
Packing Weight	8.2kg
Packing Dimensions (LxDxW)	450×450×200mm
Protection	Built-in 6mA DC RCD. Only type A RCD + MCB required
Colour	Piano Black
HMI	Status LED with dedicated apps
Certification	CE Certified, CB Certification
Standards	IEC 61851-1, IEC 61851-21-2 EU RoHS Directive Compliant

A smart 7kW charger for EVs

SB7



SB7

Tech Specs

Charging Power	7.36kW at 230V
Connector Type	Type 2 or 1
Maximum Input Current	32 amps
Nominal AC Frequency	50 Hz / 60 Hz
Input Voltage	110 / 230V AC \pm 10% (1P)
Operating Temperature	From -25°C to +55°C
Relative Humidity	0-95%
Ingress Protection	IP65
Cable Length	Up to 5m (Standard). Other lengths optional.
Impact Protection	IK08
Dimensions (DxW)	320×90mm
Weight (including cable)	3.5kg
Wireless Communication	Wi-Fi
Communication Protocol	OCPP 1.6j
Storage Temperature	From -40°C to 85°C
Packing Weight	3.85kg
Packing Dimensions (LxDxW)	385×385×100mm
Units per Pallet	99
Protection	Built-in 6mA DC RCD. Only type A RCD + MCB required
User Interface	LED
Certification	CE Certified, CB Certification
Standards	IEC 61851-1, IEC 61851-21-2 EU RoHS Directive Compliant