

Installation Instructions:

SCOYSTER // Oyster Light, 30W LED 3600lm, 420mm diameter x 28mm depth, CCT3 3000K/4000K/5700K, IP20

Product Specification	
Part Code	SCOYSTER
Colour Temp	3000K 4000K 5700K
Lumen Output	3600lm
IP Rating	IP20
Power	30W
Beam Angle	100°
CRI	>85
Voltage Rating	220-240V~ 50Hz
LED Lamp Life (L70)	30,000 Hrs
Dimmable	No
Operating Temp	-10°C to 40°C
Electrical Class	Class II - Double Insulated

These luminaires comply with AS/NZS 69598.2.1 for surface mounting to ceilings.



Not Dimmable

Installation Method

Read instructions and check you have all the tools and accessories to complete the installation correctly.

1. Isolate the mains power supply before starting the installation.
2. Select position for installation.
3. Remove central mount bracket, align on ceiling, and mark the appropriate positions for the mounting screws (See Fig 1).
4. Drill and insert ceiling plugs, and central hole for the cable and pull through ready for termination. (See Fig 2).
5. Fasten the mounting bracket to the ceiling as per diagram, then after removing the terminal cover by loosening the 4 screws to expose the terminals. Terminate the cables for Active to the L terminal and Neutral the N terminal. Make sure the outer insulation from the cable for both fixed wiring and from the light are captured under the terminal cover and tighten down the 4 screws as shown (See fig 3).
6. Connect wire trace strain relief to help support the lamp to the bracket. (See Fig 4)
7. Connect lamp wires into the terminals and ensure secured.
8. Make sure selected CCT colour (See Fig 3) is set on the selector switch (See sticker marked on product)
9. Align lamp body onto the bracket and push up against ceiling (See Fig 4, 5 and 6) and rotate to lock in place.
10. Restore the power supply, switch on and test for correct operation.

Important Information

It is recommended that luminaires be installed and fitted by a qualified electrician, ensuring the installation complies to the current building regulations. These products are designed for connection to a 220-240V~50Hz supply.

Trader will not accept responsibility for any claims arising from incorrect installation or application.

If cleaning is necessary, ensure product is switched off and only wipe the accessible lens and housing with a damp cloth and dry off using a dry lint free cloth.

Warning

Caution no user serviceable parts contained, risk of electric shock if dismantled. Cutting cables or damaging components will void warranty.

Check whether the product has been damaged in transport. Do not operate or install any product which appears damaged in any way. Return the complete product to place of purchase for inspection or replacement.

Warranty

This product has been manufactured to the highest quality standards. This product is warranted to the original purchaser and is not transferable.

The product is guaranteed to be free from defects in workmanship and parts for a period of 5 Years from the date of purchase, for full warranty detail please refer to www.gsme.com.au

Installation Instructions:

SCOYSTER // Oyster Light, 30W LED 3600lm, 420mm diameter x 28mm depth, CCT3 3000K/4000K/5700K, IP20

