

CLSWVA1GMW CLSWVA2GMW

*See current catalogue for further detail

Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended. It is important to ensure that switches are turned off before cleaning.




Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

Do not wash the cover plates in water over 60°C.




Clouded Leopard Range of Architrave Switches

- Switches are rated 16AX/20A 250V~
- Uses brass tunnel terminals that have the screws backed out for easier installation of cabling. Switches are two way with looping terminal and suit 4 x 1.5mm² cabling with 4.1mm bore
- Slotted head screws for the terminals
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Standard colour is Matt White. Matt Black also stocked - please check availability
- Approved to AS/NZS60669-1
- Typical example of size seen below:



example of cutting template supplied

CLSWVA1GMW



example of cutting template supplied

CLSWVA2GMW

Catalogue Number	Description
CLSWVA1GMW	Switch Vertical Architrave 1 Gang, 16AX/20A 250V~ Matt White
CLSWVA2GMW	Switch Vertical Architrave 2 Gang, 16AX/20A 250V~ Matt White

When ordering MATT BLACK product add "MBK" at end of catalogue number, ie CLSWVA1GMBK

MEERKAT 

MEERKAT Switch Mechanisms are used for all switch plates. Please refer to Meerkat Mech Matrix for range compatibility.

Certification Number:
GMA-507879-EA

GSM Electrical (Australia) Pty Ltd
Level 2, 142-144 Fullarton Road, Rose Park SA 5067
P: 1300 301 838 E: service@gsme.com.au
www.gsme.com.au



Data Specification Sheet
February 2023