

COPP2USB2G COPP2USB2GBK COPP2USB2GAC COPP2USB2GACBK COPP2USB2GCC COPP2USB2GCCBK

*See current catalogue for further detail

Page 2 of 2


Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended. It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.


Do not wash the cover plates in water over 60°C.



Cougar Range of USBs


COPP2USB2G

- USB outlet approved to AS/NZS 60950.1
- Electrical power point approved to AS/NZS 3112
- The rating for the USB is 3.4A at 5V when one device is inserted, then it divides the output when both USB ports are in use.
- Fits standard wall boxes and mounting accessories
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Uses brass tunnel terminals that have the screws backed out for easier installation of cabling. Power point terminals have 6mm bore to suit 4 x 2.5mm² cable
- Standard colour is white. Black also stocked - please check availability



COPP2USB2GAC

- Suitable for USB Type C applications up to 3 Amp at 5V.
- Ideal for phones that utilise USB Type C connections.
- Not suitable for laptops or other devices requiring greater output than 3 Amp at 5V.
- USB outlet approved to AS/NZS 60950.1
- Electrical power point approved to AS/NZS 3112
- The rating for the USB is 3.4A at 5V when one device is inserted, then it divides the output when both USB ports are in use.
- Fits standard wall boxes and mounting accessories
- Full cover plate
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Standard colour is white. Black also stocked - please check availability



Catalogue Number	Description
COPP2USB2G	Fully Integrated Dual USB Charger Power Point
COPP2USB2GBK	Fully Integrated Dual USB Charger Power Point, Black
COPP2USB2GAC	Power Point Switched 2 Gang 10A 250V ac USB Charger Integrated Type A and C PD20W LHS or 5V 3A 18W RHS or Dual 15W Shared Output
COPP2USB2GACBK	Power Point Switched 2 Gang 10A 250V ac USB Charger Integrated Type A and C PD20W LHS or 5V 3A 18W RHS or Dual 15W Shared Output Black

Certification Numbers:

COPP2USB2G: GMA-508273-EA
COPP2USB2GAC: TBC

GSM Electrical (Australia) Pty Ltd

Level 2, 142-144 Fullarton Road, Rose Park SA 5067
P: 1300 301 838 F: 1300 301 778 E: service@gmse.com.au
www.gmse.com.au

