

WOSBWP9 WOSBWP12 WOSBWP18 WOSBWP24

*See current catalogue for further detail



Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.



Wolverine Outdoor Switchboards

- The WOSBWP9, WOSBWP12, WOSBWP18 and WOSBWP24 are designed for outdoor surface mounting use only and intended for use to accommodate circuit protection devices such as circuit breakers; RCDs, isolating switches, surge/over-voltage protection and other such products.
- They are intended for use in domestic or commercial applications.
- They MUST be installed by a licensed electrician and follow AS/NZS3000 wiring rules.
- They comply and have been tested in accordance with AS/NZS61439.3
- IP65 from the front surfaces when mounted to AS 60529.
- Ik_p: 17kA for the enclosure assembly.
- Class 2 assembly.
- 100A rated assembly and contains Neutral and Earth bars with double rows of screws.
- Parts pack includes 80A rated bus bar, sticker labelling pack in red and green for non-RCD protected and RCD protected circuit identification, pole fillers (full and half DIN module sizes)

INTERFACE CHARACTERISTIC

Voltage ratings

Rated voltage (U_n): 415V

Rated operational voltage (U_e): 415V

Rated insulation voltage (U_i): 1000V

Rated impulse withstand voltage of assembly (U_{imp}): 4000V

Complies with minimum overvoltage category III according IEC 60364-4-44

Current ratings

Rated current of the ASSEMBLY (I_{nA}): 100A

Rated peak withstand current (Ik_p): 17kA

Rated conditional short-circuit current of an ASSEMBLY (I_{cc}): 10kA

Rated diversity factor (RDF) 1-0.9

Rated frequency (f_n) 50Hz

Pollution degree: 2

Fixed stationary installation.

Installation to be carried out by a skilled licensed electrician

Mechanical impact protection: IK05

For protection against electric shock requires screws to be removed to access live parts.

Type B distribution board

The rating of loose busbars. 80A end fed or 100A centre feed.

Neutral link rating : 100A

Overall dimensions:

9 module: 219mm(w) x 200mm(h) x 101mm(d)

12 module: 273mm(w) x 230mm(h) x 101mm(d),

18 module: 381mm(w) x 250mm(h) x 114mm(d),

24 module: 273mm(w) x 400mm(h) x 114mm(d)

Weight:

9 module: 0.752g,

12 module: 1.103g,

18 module: 1.825kg,

24 module: 2.308kg



Catalogue Number	Description
WOSBWP9	Switchboard Surface Mount Weatherproof 9 Way 100A 415V ac IP65 with Transparent Grey Door for Outdoor Use
WOSBWP12	Switchboard Surface Mount Weatherproof 12 Way 100A 415V ac IP65 with Transparent Grey Door for Outdoor Use
WOSBWP18	Switchboard Surface Mount Weatherproof 18 Way 100A 415V ac IP65 with Transparent Grey Door for Outdoor Use
WOSBWP24	Switchboard Surface Mount Weatherproof 24 Way 100A 415V ac IP65 with Transparent Grey Door for Outdoor Use

Certification Number:

GMA-521618

GSM Electrical (Australia) Pty Ltd

Level 2, 142-144 Fullarton Road, Rose Park SA 5067

P: 1300 301 838 F: 1300 301 778 E: service@gmse.com.au

www.gmse.com.au

